

COYLE SUPPLY, INC

Pipe Size (inches)	Outside Diameter (inches)	Identification			Wall Thickness - <i>t</i> - (inches)	Inside Diameter - <i>d</i> - (inches)	Area of Metal (square inches)	Transverse Internal Area		Moment of Inertia - <i>I</i> - (inches)	Weight Pipe (pounds per foot)	Weight Water (pounds per foot)	External Surface (square feet per foot of pipe)	Elastic Section Modulus (in ³)
		Steel		<i>A</i> (square feet)										
		Iron Pipe Size	Pipe Schedule					<i>a</i> (square inches)						
1/8	0.405	.	.	10S	.049	.307	.0548	.0740	.00051	.00088	.19	.032	.106	.00437
				40S	.068	.269	.0720	.0568	.00040	.00106	.025	.106	.00523	
				80S	.095	.215	.0925	.0364	.00025	.00122	.016	.106	.00602	
1/4	0.540	.	.	10S	.065	.410	.0970	.1320	.00091	.00279	.33	.057	.141	.01032
				40S	.088	.364	.1250	.1041	.00072	.00331	.045	.141	.01227	
				80S	.119	.302	.1574	.0716	.00050	.00377	.031	.141	.01395	
3/8	0.675	.	.	10S	.065	.545	.1246	.2333	.00162	.00586	.42	.101	.178	.01736
				40S	.091	.493	.1670	.1910	.00133	.00729	.083	.178	.02160	
				80S	.126	.423	.2173	.1405	.00098	.00862	.061	.178	.02554	
1/2	0.840	.	.	5S	.065	.710	.1583	.3959	.00275	.01197	.54	.172	.220	.02849
				10S	.083	.674	.1974	.3568	.00248	.01431	.155	.220	.03407	
				40S	.109	.622	.2503	.3040	.00211	.01709	.132	.220	.04069	
3/4	1.050	.	.	80S	.147	.546	.3200	.2340	.00163	.02008	1.09	.102	.220	.04780
				.	.187	.466	.3836	.1706	.00118	.02212	.074	.220	.05267	
				160	.294	.252	.5043	.050	.00035	.02424	.022	.220	.05772	
1	1.315	.	.	5S	.065	.920	.2011	.6648	.00462	.02450	.69	.288	.275	.04667
				10S	.083	.884	.2521	.6138	.00426	.02969	.266	.275	.05655	
				40S	.113	.824	.3326	.5330	.00371	.03704	.231	.275	.07055	
1 1/4	1.660	.	.	80S	.154	.742	.4335	.4330	.00300	.04479	1.47	.188	.275	.08531
				.	.219	.612	.5698	.2961	.00206	.05269	.128	.275	.10036	
				160	.358	.599	.10760	.282	.00196	.05792	.064	.275	.11032	
1 1/2	1.915	.	.	5S	.065	1.185	.2553	1.1029	.00766	.04999	.87	.478	.344	.07603
				10S	.109	1.097	.4130	.9452	.00656	.07569	.409	.344	.11512	
				40S	.133	1.049	.4939	.8640	.00600	.08734	.375	.344	.1328	
2	2.375	.	.	80S	.179	.957	.6388	.7190	.00499	.1056	2.17	.312	.344	.1606
				.	.250	.815	.8365	.5217	.00362	.1251	.230	.344	.1903	
				160	.358	.599	1.0760	.282	.00196	.1405	.122	.344	.2136	
2 1/2	3.063	.	.	5S	.065	1.530	.3257	1.839	.01277	.1038	1.11	.797	.435	.1250
				10S	.109	1.442	.4717	1.633	.01134	.1605	.708	.435	.1934	
				40S	.140	1.380	.6685	1.495	.01040	.1947	.649	.435	.2346	
3	4.313	.	.	80S	.191	1.278	.8815	1.283	.00891	.2418	3.00	.555	.435	.2913
				.	.250	1.160	1.1070	1.057	.00734	.2839	.458	.435	.3421	
				160	.382	.896	1.534	.630	.00438	.3411	.273	.435	.4110	

COYLE SUPPLY, INC

Pipe Size (inches)	Outside Diameter (inches)	Identification			Wall Thickness - <i>t</i> - (inches)	Inside Diameter - <i>d</i> - (inches)	Area of Metal (square inches)	Transverse Internal Area		Moment of Inertia - <i>I</i> - (inches)	Weight Pipe (pounds per foot)	Weight Water (pounds per foot)	External Surface (square feet per foot of pipe)	Elastic Section Modulus (in ³)
		Steel		<i>A</i> (square feet)										
		Iron Pipe Size	Pipe Schedule					<i>a</i> (square inches)						
1 1/2	1.900	.	.	5S	1.770	.3747	2.461	.01709	.1579	1.28	1.066	.497	.1662	
				10S	1.682	.6133	2.222	.01543	.2468	2.09	.963	.497	.2598	
				40S	1.610	.7995	2.036	.01414	.3099	2.72	.882	.497	.3262	
				80S	1.500	1.068	1.767	.01225	.3912	3.63	.765	.497	.4118	
				.	1.338	1.429	1.406	.00976	.4824	4.86	.608	.497	.5078	
				.	1.100	1.885	.950	.00660	.5678	6.41	.42	.497	.5977	
2	2.375	.	.	5S	2.245	.4717	3.958	.02749	.3149	1.61	1.72	.622	.2652	
				10S	2.157	.7760	3.654	.02538	.4992	2.64	1.58	.622	.4204	
				40S	2.067	1.075	3.355	.02330	.6657	3.65	1.45	.622	.5606	
				80S	1.939	1.477	2.953	.02050	.8679	5.02	1.28	.622	.7309	
				.	1.687	2.190	2.241	.01556	1.162	7.46	.97	.622	.979	
				.	1.503	2.656	1.774	.01232	1.311	9.03	.77	.622	1.104	
2 1/2	2.875	.	.	5S	2.709	.7280	5.764	.04002	.7100	2.48	2.50	.753	.4939	
				10S	2.635	1.039	5.453	.03787	.9873	3.53	2.36	.753	.6868	
				40S	2.469	1.704	4.788	.03322	1.530	5.79	2.07	.753	1.064	
				80S	2.323	2.254	4.238	.02942	1.924	7.66	1.87	.753	1.339	
				.	2.125	2.945	3.546	.02463	2.353	10.01	1.54	.753	1.638	
				.	1.771	4.028	2.464	.01710	2.871	13.69	1.07	.753	1.997	
3	3.500	.	.	5S	3.334	.8910	8.730	.06063	1.301	3.03	3.78	.916	.7435	
				10S	3.260	1.274	8.347	.05796	1.822	4.33	3.62	.916	1.041	
				40S	3.068	2.228	7.393	.05130	3.017	7.58	3.20	.916	1.724	
				80S	2.900	3.016	6.605	.04587	3.894	10.25	2.6	.916	2.225	
				.	2.624	4.205	5.408	.03755	5.032	14.32	2.35	.916	2.876	
				.	2.300	5.466	4.155	.02885	5.993	18.58	1.80	.916	3.424	
3 1/2	4.000	.	.	5S	3.834	1.021	11.545	.08017	1.960	3.48	5.00	1.047	.9799	
				10S	3.760	1.463	11.104	.07711	2.755	4.97	4.81	1.047	1.378	
				40S	3.548	2.680	9.886	.06870	4.788	9.11	4.29	1.047	2.394	
				80S	3.364	3.678	8.888	.06170	6.280	12.50	3.84	1.047	3.140	
				.	4.334	1.152	14.75	.10245	2.810	3.92	6.39	1.178	1.249	
				.	4.260	1.651	14.25	.09898	3.963	5.61	6.18	1.178	1.761	
4	4.500	.	.	5S	4.260	1.651	14.25	.09898	3.963	5.61	6.18	1.178	1.761	
				10S	4.026	3.174	12.73	.08840	7.233	10.79	5.50	1.178	3.214	
				40S	3.826	4.407	11.50	.07986	9.610	14.98	4.98	1.178	4.271	
				80S	3.624	5.595	10.31	.0716	11.65	19.0	4.47	1.178	5.178	
				.	3.438	6.621	9.28	.0645	13.27	22.51	4.02	1.178	5.898	
				.	3.152	8.101	7.80	.0542	15.28	27.54	3.38	1.178	6.791	

COYLE SUPPLY, INC

Pipe Size (inches)	Outside Diameter (inches)	Identification			Wall Thickness - <i>t</i> - (inches)	Inside Diameter - <i>d</i> - (inches)	Area of Metal (square inches)	Transverse Internal Area		Moment of Inertia - <i>I</i> - (inches)	Weight Pipe (pounds per foot)	Weight Water (pounds per foot)	External Surface (square feet per foot of pipe)	Elastic Section Modulus (in ³)																																																																							
		Iron Pipe Size	Steel Pipe Schedule	Stainless Steel Schedule No.				<i>a</i> (square inches)	<i>A</i> (square feet)																																																																												
															Steel Schedule																																																																						
5	5.563109	1.868	22.44	.1558	6.947	6.36	9.72	1.456	2.498																																																																								
														STD	40	10S	.	22.02	7.77	9.54	1.456	3.029																																																															
																							XS	80	40S	.	20.01	14.62	8.67	1.456	5.451																																																						
																																.	120	80S	.	18.19	20.78	7.88	1.456	7.431																																													
																																									.	160	.	.	16.35	27.04	7.09	1.456	9.250																																				
																																																		XXS	.	.	.	14.61	32.96	6.33	1.456	10.796																											
																																																											12.97	38.55	5.61	1.456	12.090																		
																																																																				32.24	7.60	13.97	1.734	3.576									
																																																																													31.74	9.29	13.75	1.734	4.346
XS	80	40S	.	26.07	28.57	11.29	1.734	12.22																																																																													
									.	120	80S	.	23.77	36.39	10.30	1.734	14.98																																																																				
																		.	160	.	.	21.15	45.35	9.16	1.734	17.81																																																											
																											XXS	.	.	.	18.84	53.16	8.16	1.734	20.02																																																		
																																				55.51	9.93	24.06	2.258	6.131																																									
																																													54.48	13.40	23.61	2.258	8.212																																
																																																						.	20	10S	.	51.85	22.36	22.47	2.258	13.39																							
																																																															.	30	.	.	51.16	24.70	22.17	2.258	14.69														
																																																																								STD	40	40S	.	50.03	28.55	21.70	2.258	16.81					
																																																																																	.	60	.	.	47.94
XS	80	80S	.	45.66	43.39	19.78	2.258	24.51																																																																													
									.	100	.	.	43.46	50.95	18.83	2.258	28.14																																																																				
																		.	120	.	.	40.59	60.71	17.59	2.258	32.58																																																											
																											.	140	.	.	38.50	67.76	16.68	2.258	35.65																																																		
																																				XXS	.	.	.	37.12	72.42	16.10	2.258	37.56																																									
																																													.	160	.	.	36.46	74.69	15.80	2.258	38.48																																

COYLE SUPPLY, INC

Pipe Size (inches)	Outside Diameter (inches)	Identification			Wall Thickness - <i>t</i> - (inches)	Inside Diameter - <i>d</i> - (inches)	Area of Metal (square inches)	Transverse Internal Area		Moment of Inertia - <i>I</i> - (inches)	Weight Pipe (pounds per foot)	Weight Water (pounds per foot)	External Surface (square feet per foot of pipe)	Elastic Section Modulus (in ³)																																																																																																																																																																							
		Iron Pipe Size	Steel Pipe Schedule	Stainless Steel Schedule No.				<i>a</i> (square inches)	<i>A</i> (square feet)																																																																																																																																																																												
															Steel																																																																																																																																																																						
14	14.00156	13.688	6.78	147.15	1.0219	162.6	63.77	3.665	23.2																																																																																																																																																																								
							188	13.624	8.16	145.78	1.0124	194.6	63.17	3.665	27.8																																																																																																																																																												
																			250	13.500	10.80	13.42	143.14	.9940	255.3	62.03	3.665	36.6																																																																																																																																																
																															312	13.376	13.42	16.05	140.52	.9758	314.4	60.89	3.665	45.0																																																																																																																																				
																																											375	13.250	18.66	135.28	137.88	.9575	372.8	59.75	3.665	53.2																																																																																																																								
																																																							438	13.124	21.21	132.73	135.28	.9394	429.1	58.64	3.665	61.3																																																																																																												
																																																																			500	13.000	24.98	128.96	132.73	.9217	483.8	57.46	3.665	69.1																																																																																																
																																																																															594	12.812	31.22	122.72	128.96	.8956	562.3	55.86	3.665	80.3																																																																																				
																																																																																											750	12.500	38.45	115.49	122.72	.8522	678.3	53.18	3.665	98.2																																																																								
																																																																																																							938	12.124	44.32	109.62	115.49	.8020	824.4	50.04	3.665	117.8																																																												
																																																																																																																				1.094	11.812	50.07	103.87	109.62	.7612	929.6	47.45	3.665	132.8																																																
																																																																																																																																1.250	11.500	55.63	98.31	103.87	.7213	1027.0	45.01	3.665	146.8																																				
																																																																																																																																												1.406	11.188	8.21	192.85	98.31	.6827	1117.0	42.60	3.665	159.6																								
																																																																																																																																																							165	15.670	9.34	191.72	192.85	1.3393	257.3	83.57	4.189	32.2												
																																																																																																																																																																			188	15.624	12.37	188.69	191.72	1.3314	291.9	83.08	4.189	36.5
																																																																																																																																																																																.	.				
.312	15.376	18.41	182.65			185.69	1.2895	473.2	80.50																																																																																																																																																																								
							375	15.250	24.35	176.72	182.65	1.2684			562.1	79.12	4.189	70.3																																																																																																																																																												
																	500	15.000	31.62	169.44	176.72	1.2272			731.9	76.58	4.189	91.5																																																																																																																																																
																													656	14.688	40.14	160.92	169.44	1.1766			932.4	73.42	4.189	116.6																																																																																																																																				
																																									844	14.312	48.48	152.58	160.92	1.175			1155.8	69.73	4.189	144.5																																																																																																																								
																																																										1.031	13.938	56.56	144.50	152.58	1.0596			1364.5	66.12	4.189	170.5																																																																																																												
																																																																						1.219	13.562	65.78	135.28	144.50	1.0035			1555.8	62.62	4.189	194.5																																																																																																
																																																																																		1.438	13.124	72.10	128.96	135.28	.9394			1760.3	58.64	4.189	220.0																																																																																				
																																																																																														1.594	12.812	8.21	128.96	128.96	.8956			1893.5	55.83	4.189	236.7																																																																								

COYLE SUPPLY, INC

Pipe Size (inches)	Outside Diameter (inches)	Identification			Wall Thickness - <i>t</i> - (inches)	Inside Diameter - <i>d</i> - (inches)	Area of Metal (square inches)	Transverse Internal Area		Moment of Inertia - <i>I</i> - (inches)	Weight Pipe (pounds per foot)	Weight Water (pounds per foot)	External Surface (square feet per foot of pipe)	Elastic Section Modulus (in ³)				
		Steel		<i>A</i> (square feet)														
		Iron Pipe Size	Pipe Schedule					<i>a</i> (square inches)										
22	22.00	.	.	5S	.188	21.624	12.88	367.25	2.5503	766.2	43.80	159.14	5.760	69.7				
				10S	.218	21.564	14.92	365.21	2.5362	884.8	50.71	158.26	5.760	80.4				
		STD	XS	.	.	.250	.375	21.500	17.08	363.05	2.5212	1010.3	58.07	157.32	5.760	91.8		
						.500	.875	21.250	25.48	354.66	2.4629	1489.7	86.61	153.68	5.760	135.4		
	1.125	.1.375	21.000	33.77	346.36	2.4053	1952.5	114.81	150.09	5.760	117.5		
						.1.625	.1.875	20.250	58.07	322.06	2.2365	3244.9	197.41	139.56	5.760	295.0		
	2.125	.2.125	19.75	73.78	306.35	2.1275	4030.4	250.81	132.76	5.760	366.4		
						.2.125	.2.125	19.25	89.09	291.04	2.0211	4758.5	302.88	126.12	5.760	432.6		
	1.625	.1.875	18.75	104.02	276.12	1.9175	5432.0	353.61	119.65	5.760	493.8		
						.2.062	.2.344	18.25	118.55	261.59	1.8166	6053.7	403.00	113.36	5.760	550.3		
	2.344	.2.344	17.75	132.68	247.45	1.71840	6626.4	451.06	107.23	5.760	602.4		
						.2.344	.2.344	23.564	16.29	436.10	3.0285	1151.6	55.37	188.98	6.283	96.0		
		24	24.00	.	.	5S	.218	23.564	16.29	436.10	3.0285	1151.6	55.37	188.98	6.283	96.0		
						10S	.250	23.500	18.65	433.74	3.0121	1315.4	63.41	187.95	6.283	109.6		
				STD	XS	.	.	.375	.500	23.250	27.83	424.56	2.9483	1942.0	94.62	183.95	6.283	161.9
								.562	.688	23.000	36.91	415.48	2.8853	2549.5	125.49	179.87	6.283	212.5
.688	.969	22.876	41.39	411.00	2.8542	2843.0	140.68	178.09	6.283	237.0		
						.1.219	.1.531	22.624	50.31	402.07	2.7921	3421.3	171.29	174.23	6.283	285.1		
.969	.1.219	22.062	70.04	382.35	2.6552	4652.8	238.35	165.52	6.283	387.7		
						.1.531	.1.812	21.562	87.17	365.22	2.5362	5672.0	296.58	158.26	6.283	472.8		
.1.812	.2.062	20.938	108.07	344.32	2.3911	6849.9	367.39	149.06	6.283	570.8		
						.2.062	.2.344	20.376	126.31	326.08	2.2645	7825.0	429.39	141.17	6.283	652.1		
.2.062	.2.344	19.876	142.11	310.28	2.1547	8625.0	483.12	134.45	6.283	718.9		
						.2.344	.2.344	19.312	159.41	292.98	2.0346	9455.9	542.13	126.84	6.283	787.9		
.312	.375	25.376	25.18	505.75	3.5122	2077.2	85.60	219.16	6.806	159.8		
						.375	.500	25.250	30.19	500.74	3.4774	2478.4	102.63	216.99	6.806	190.6		
STD	XS			.	.	.500	.625	25.000	40.06	490.87	3.4088	3257.0	136.17	212.71	6.806	250.5		
						.625	.625	27.376	27.14	588.61	4.0876	2601.0	92.26	255.07	7.330	185.8		
.312	.375	27.250	32.54	583.21	4.0501	3105.1	110.64	252.73	7.330	221.8				
				.500	.625	27.000	43.20	572.56	3.9761	4084.8	146.85	248.11	7.330	291.8				
.625	.625	26.750	53.75	562.00	3.9028	5037.7	182.73	243.53	7.330	359.8				
				.625	.625	29.500	23.37	683.49	4.7465	2585.2	79.43	296.18	7.854	172.3				
.312	.375	29.376	29.10	677.76	4.7067	3206.3	98.93	293.70	7.854	213.8				
				.375	.500	29.250	34.90	671.96	4.6664	3829.4	118.65	291.18	7.854	255.3				
.500	.625	29.000	46.34	660.52	4.5869	5042.2	157.53	286.22	7.854	336.1				
				.625	.625	28.750	57.68	649.18	4.5082	6224.0	196.08	281.31	7.854	414.9				

COYLE SUPPLY, INC

Pipe Size (inches)	Outside Diameter (inches)	Identification			Wall Thickness - <i>t</i> - (inches)	Inside Diameter - <i>d</i> - (inches)	Area of Metal (square inches)	Transverse Internal Area		Moment of Inertia - <i>I</i> - (inches)	Weight Pipe (pounds per foot)	Weight Water (pounds per foot)	External Surface (square feet per foot of pipe)	Elastic Section Modulus (in ³)
		Steel		<i>A</i> (square feet)										
		Iron Pipe Size	Pipe Schedule					<i>a</i> (square inches)						
32	32.00	.	10	.	.312	31.376	31.06	773.19	5.3694	3898.9	105.59	335.05	8.378	243.7
			STD	.	.375	31.250	37.26	766.99	5.3263	4658.5	126.66	332.36	8.378	291.2
			XS	20	.500	31.000	49.48	754.77	5.2414	6138.6	168.21	327.06	8.378	383.7
			.	30	.625	30.750	61.60	742.64	5.1572	7583.4	209.43	321.81	8.378	474.0
34	34.00	.	10	.	.344	33.312	36.37	871.55	6.0524	5150.5	123.65	377.67	8.901	303.0
			STD	.	.375	33.250	39.61	868.31	6.0299	5599.3	134.67	376.27	8.901	329.4
			XS	20	.500	33.000	52.62	855.30	5.9396	7383.5	178.89	370.63	8.901	434.3
			.	30	.625	32.750	65.53	842.39	5.8499	9127.6	222.78	365.03	8.901	536.9
36	36.00	.	10	.	.312	35.376	34.98	982.90	6.8257	5569.5	118.92	425.92	9.425	309.4
			STD	.	.375	35.250	41.97	975.91	6.7771	6658.9	142.68	422.89	9.425	369.9
			XS	20	.500	35.000	55.76	962.11	6.6813	8786.2	189.57	416.91	9.425	488.1
			.	30	.625	34.750	69.46	948.42	6.5862	10868.4	236.13	417.22	9.425	603.8
42	42.00	.	10	.	.750	34.500	83.06	934.82	6.4918	12906.1	282.35	405.09	9.425	717.0
			STD	.	.375	41.250	49.08	1336.3	.	10627	167	579.3	10.99	506.1
			XS	20	.500	41.000	65.18	1320.2	.	14037	222	572.3	10.99	668.4
			.	30	.625	40.720	81.28	1304.1	.	17373	276	565.4	10.99	827.3
42	42.00	.	40	.	.750	40.500	97.23	1288.2	.	20689	330	558.4	10.99	985.2

1 in (inch) = 25.4 mm

STD, XS and XXS

To distinguish different weights of pipe, three long standing traditional designations are used: standard wall (Std.), extra strong wall (XS), and double extra strong wall (XXS). These last two designations are sometimes referred to as extra heavy wall (XH), and double extra heavy wall (XXH).

Pipe Size (inches)	Outside Diameter		Identification		Wall Thickness - t - (inches)	Inside Diameter - d - (inches)	Area of Metal (square inches)	Transverse Internal Area		Moment of Inertia - I - (inches)	Weight Pipe (pounds per foot)	Weight Water (pounds per foot)	External Surface (square feet per foot of pipe)	Elastic Section Modulus (in ³)
	Iron Pipe Size	Pipe Schedule	Steel	Stainless Steel Schedule No.				a (square inches)	A (square feet)					

The following is for theoretical information only. Users are responsible for determining correct suitability of pipe for the intended application.

Pressure Determinations: Barlow's Formula is commonly used to determine:

1. Internal Pressure at Minimum Yield

2. Ultimate Bursting Pressure

3. Maximum Allowable Working Pressure

4. Mill Hydrostatic Test Pressure

This formula is expressed as $P = 2St$ where: P = Pressure, psig, I = Nominal wall thickness, inches D = Outside Diameter, inches

S = Allowable Stress, psi, which depends on the pressure being determined

To illustrate, assume a piping systems 8 5/8" O.D. x .375" wall has a specified minimum yield strength (SMYS) of 35,000 psi and a specified minimum tensile strength of 80,000 psi.

For 1. Internal Pressure of Minimum Yield

S = SMYS (35,000) psi and

$P = 2St = (2)(35,000)(0.375)$

D 8.625 = 3043 or 3040 psig (rounded to nearest 10 psig)

For 2. Ultimate Bursting Pressure

S = Specified Minimum Tensile Strength (60,000 psi) and

$P = 2St = (2)(60,000)(0.375)$

D 8.625 = 5217 or 5220 psig (rounded to nearest 10 psig)

Pipe Size (inches)	Outside Diameter (inches)		Identification		Wall Thickness - t - (inches)	Inside Diameter - d - (inches)	Area of Metal (square inches)	Transverse Internal Area		Moment of Inertia - I - (inches)	Weight Pipe (pounds per foot)	Weight Water (pounds per foot)	External Surface (square feet per foot of pipe)	Elastic Section Modulus (in ³)
	Iron Pipe Size	Steel	Stainless Steel Schedule No.	Pipe Schedule				a (square inches)	A (square feet)					

For 3. Maximum Allowable Working Pressure (MAOP)

$S = SMYS$ (35,000 psi) reduced by a design factor, usually 0.72 and

$$P = 2St = \frac{2}{(35,000 \times 2)}(0.375)$$

$$D \ 8.625 = 2191 \text{ or } 2190 \text{ psig (rounded to nearest 10 psig)}$$

For 4. Mill Hydrostatic Test Pressure

$S = SMYS$ (35,000 psi) reduced by a factor depending on O.D., grade (0.60 for 8 5/8" O.D., grade B) and

$$P = 2St = \frac{2}{(35,000 \times 0.60)}(0.375)$$

$$D \ 8.625 = 1826 \text{ or } 1830 \text{ psig (rounded to nearest 10 psig)}$$

Wall Thickness

Barlow's Formula is also useful in determining the wall thickness required for a piping system. To illustrate, assume a piping system has been designed with the following criteria:

1. A working pressure of 2,000 psi (P)
2. The pipe to be used is 8 5/8" O.D. (D) specified to ASTM A53 grade B (SMYS - 35,000 psi)

Rearranging Barlow's Formula to solve for wall thickness gives:

$$t = \frac{PD}{2S} = \frac{(2,000)(8.625)}{2(35,000)} = 0.246" \text{ wall}$$

$$2S(2)(35,000)$$

pipe is identical; however, the inside diameter of the extra-strong is smaller than the inside diameter of the standard weight because the wall thickness is greater in the extra-strong pipe.

COYLE SUPPLY, INC

Pipe Size (inches)	Outside Diameter (inches)		Identification		Wall Thickness - t - (inches)	Inside Diameter - d - (inches)	Area of Metal (square inches)	Transverse Internal Area		Moment of Inertia - I - (inches)	Weight Pipe (pounds per foot)	Weight Water (pounds per foot)	External Surface (square feet per foot of pipe)	Elastic Section Modulus (in ³)
	Iron Pipe Size	Pipe Schedule	Steel	Stainless Steel Schedule No.				a (square inches)	A (square feet)					

5. WATER DISCHARGE MEASUREMENTS: To calculate the volume being displaced through a pipe or the amount of volume of an irrigation well, the following formula is applicable:

$$Q = 3.61 A H \% Y$$

Where:

Q = Discharge in Gallons per minutes

A = Area of the pipe, inches squared

H = Horizontal measurement, inches

Y = vertical measurement, inches

Example: Calculate the discharge of a 10" pipe which has an area of 78.50 in², a horizontal measurement of 12" and a vertical measurement of 12".

$$Q = 3.61 A H$$

$\% Y$

$$Q = 3.61 (78.50) (12)$$

$$0.12$$

$$Q = 3400.62$$

$$3.464$$

$$Q = 981.70 \text{ gallons per minute}$$

distance horizontally to the point of the 12" vertical measurement.